RYNAN®
PRINTING



R60 & REACH

CONTROLLER **PRINTHEAD**

Touch Screen Controller With Multiple Funai TIJ Print Heads

R60 REACH



TECHNICAL SPECIFICATIONS

Printing Technology	Funai TIJ
Controller Dimensions	305.6x 200.9 x 64.2 mm
Printhead Dimensions	136.2 x 64.6 x 83.1 mm (1 Printhead) 136.2 x 99.5 x 95.5 mm (2 Printheads) 136.2 x 134.4 x 107.9mm (3 Printheads) 136.2 x 166.7 x 120.2 mm (4 Printheads) 136.2 x 145.1 x 251.3 mm (5 Printheads)
Controller Weight	2750g
Print Head Weight	430g
Display	10" LCD Touch Screen
Power Supply	AC 100V–240V, 50/60H, DC 24V 9.2A
Resolutions	Max 300 DPI
Print Speed	Up to 45m/min at 300x200 DPI
Density	3 levels
Throw Distance	Up to 10mm

FEATURES

Wide Range Of Print Types	• Text, Counter • Box/Lot • Datetime • Expiry Date • Julian Date • Shiftcode • Image • Database 1D & 2D Barcodes (Code 11, Code 39, Code 128, EAN, QR, Datamatrix, GS1 Datamatrix)
Printable Height	Maximum 81mm / 6 heads
External Connections	• External Sensor, Encoder and Alarm beacon
Template Length	Standard 2m, Support up to 10m
Database	TXT, CSV
Advance Features	• Free design in template up to 81mm (6 head) • POD (Print online data) Integrate with other devices (PLC, Camera, Checkweigher...) via RJ45 • Real-time Printing • WYSIWYG (what you see is what you get) • Data upload, Backup & Recovery via USB
Printable Characters	Windows true fonts - Free design in template up to 81mm (6 head)
Print Languages	English (default),Vietnamese, Chinese (PRC), Turkish, Korean, Russian, Japanese, Hebrew, Spanish, Thai, Portuguese and Arabic
System Languages	English (default), German, Vietnamese, Chinese, Korean, Russian, Turkish, Portuguese, Spanish, Polish, Greek and Italian (and others)

REACH PRINTHEAD COMBINATION

Choice of up to 6 independent printheads



